

ELECTRICITY DEMAND FORECASTING USING A SARIMA-MULTIPLICATIVE SINGLE NEURON HYBRID MODEL

PRONÓSTICO DE LA DEMANDA DE ELECTRICIDAD USANDO UN MODELO HÍBRIDO SARIMA-NEURONA SIMPLE MULTIPLICATIVA

JUAN DAVID VELÁSQUEZ HENAO

Profesor Titular, Escuela de Sistemas, Universidad Nacional de Colombia, Medellín, jdvelasq@unal.edu.co

VIVIANA MARIA RUEDA MEJIA

Analista de Información, XM S.A. E.S.P., Medellín, vrueda@xm.com.co

CARLOS JAIME FRANCO CARDONA

Profesor Titular, Escuela de Sistemas, Universidad Nacional de Colombia, Medellín, cijfranco@unal.edu.co

Received for review September 07th, 2012, accepted April 22th, 2013, final version July, 12th, 2013

ABSTRACT: The combination of SARIMA and neural network models are a common approach for forecasting nonlinear time series. While the SARIMA methodology is used to capture the linear components in the time series, artificial neural networks are applied to forecast the remaining nonlinearities in the shocks of the SARIMA model. In this paper, we propose a simple nonlinear time series forecasting model by combining the SARIMA model with a multiplicative single neuron using the same inputs as the SARIMA model. To evaluate the capacity of the new approach, the monthly electricity demand in the Colombian energy market is forecasted and compared with the SARIMA and multiplicative single neuron models.

KEYWORDS: SARIMA; artificial neural networks; time series prediction; energy demand; energy markets; nonlinear models.

RESUMEN: La combinación de modelos SARIMA y redes neuronales son una aproximación común para pronosticar series de tiempo no lineales. Mientras la metodología SARIMA es usada para capturar las componentes lineales en la serie de tiempo, las redes neuronales artificiales son aplicadas para pronosticar las no-linealidades remanentes en los residuos del modelo SARIMA. En este artículo, se propone un modelo simple no lineal para el pronóstico de series de tiempo obtenido por la combinación de un modelo SARIMA y una neurona simple multiplicativa que usa las mismas entradas del modelo SARIMA. Para evaluar la capacidad de la nueva aproximación, la demanda mensual de electricidad en el mercado de energía de Colombia es pronosticada y comparada con los modelos SARIMA y la neurona simple multiplicativa.

PALABRAS CLAVE: SARIMA; redes neuronales artificiales, predicción de series de tiempo, demanda de energía; mercados energéticos; modelos no lineales.

1. INTRODUCTION

Forecasting nonlinear time series is a common application for artificial neural networks [1]. An approach for building hybrid methods with artificial neural networks is to suppose that a nonlinear time series is composed of linear and nonlinear components as follows [3,5,7]:

$$y_t = L_t + N_t \quad (1)$$

where y_t denotes the original time series, L_t is the non-stationary linear component and N_t is the nonlinear

component. Usually, the Box-Jenkins methodology [2] is used to specify L_t as an (seasonal) ARIMA model and to calculate the residuals of the time series as:

$$e_t = y_t - \hat{L}_t \quad (2)$$

An artificial neural network is used to approximate the nonlinear component N_t . By using this simple idea, several approaches have been proposed: Zhang [3] and Aladag et al. [7] use the SARIMA model residuals as inputs for an artificial neural network; while a multilayer perceptron neural network is used in [3], and Elman's recurrent neural network is used in [7];

Tseng et al. [5] use the residuals and the forecasts \hat{L}_t of a SARIMA model as inputs of multilayer perceptron.

The rationale of these approaches is that the L_t component (the ARIMA model) is able to represent the linear components in the time series as the trend or seasonal patterns, while the N_t component captures the remaining nonlinearities in the data.

In all previous works [3,5,7], the first stage consists of obtaining the specification of a SARIMA model. In the second stage, the parameters (and fitted residuals) of the SARIMA model remain fixed while only the parameters of the artificial neural network are estimated.

However, previous approaches have two limitations: Firstly, the parameters of the hybrid model (1) are not optimal because the parameters of the SARIMA and the artificial neural network are not estimated simultaneously. Secondly, the configuration (inputs, processing layers, and number of neurons for layer) of the artificial neural network is done by a trial and error process [8] [9].

In the next section, we propose a new hybrid model to overcome these limitations. In Section 3, an application case is presented. In Section 4, we summarize the results.

2. PROPOSED HYBRID MODEL

In the generalized single multiplicative neuron (GSMN) model [4], the current value of a time series is obtained as a function of previous values:

$$y_t = N_t = g \left[\prod_{i=1}^p (w_i y_{t-i} + b_i) \right] \quad (3)$$

Where $g(u)$ is the activation function and p is the order of the nonlinear autoregressive model. We chose this model for the following reasons:

- a) The specification process of a GSMN corresponds to selecting only the appropriate lags of the time series modeled. For the standard multilayer perceptron, the specification is more difficult: it is necessary to specify the number of hidden layers and the number of neurons per layer in addition to the appropriate lags.
- b) The GSMN require fewer parameters than the standard multilayer perceptron and it has a better generalization capability as is demonstrated in the empirical evidence presented in [4]. As a consequence, a fewer number of iterations of the optimization algorithm are necessary to converge to the optimum of the loss function.

In our approach, we fuse a SARIMA model with a GSMN using the same inputs as the SARIMA component. Thus, we specify the GSMN model as:

$$N_t = g \left[\prod_{i \in \Phi} (w_i y_{t-i} + b_i) \prod_{j \in \Theta} (u_j e_{t-j} + c_j) - 1 \right] \quad (4)$$

where: Φ is the set that contains the same lags of y_t used for the SARIMA model; Θ is the set that contains the same lags of e_t used for the SARIMA model; and $g(u) = \tanh u$.

In (4), the term $(u_j e_{t-j} + c_j)$ is introduced with the aim of representing the nonlinear dynamics of the moving average component. Note that when we impose the restrictions $w_i = u_j = 0$ and $b_i = c_j = 1$, then $N_t =$

$$\begin{aligned} & \tanh \left[\prod_{i \in \Phi} (0 \cdot y_{t-i} + 1) \prod_{j \in \Theta} (0 \cdot e_{t-j} + 1) - 1 \right] \\ &= \tanh \left[\prod_{i \in \Phi} 1 \prod_{j \in \Theta} 1 - 1 \right] = \tanh 0 \\ &= 0 \end{aligned} \quad (5)$$

and the proposed model is reduced to the SARIMA approach.

The proposed approach is a general nonlinear model for time series forecasting. The SARIMA component (L_t) is a well-established and understood method for dealing with the linear components of the time series and allows for the modeler to represent characteristics such as the trend or seasonal patterns. The GSMN component (4) captures the remaining nonlinearities present in the data, which are not captured by the SARIMA methodology. The steps for building the model are described as follows:

Stage 1. Scaling: we scale the time series y_t in the interval $[-1, +1]$ due to the limitation in the range of $g(u) = \tanh u$.

Stage 2. Linear modeling: We obtain the specification of a SARIMA model for the time series using a well-established methodology. In other words, we specify the L_t model. In this stage, the lags for y_t and e_t are obtained.

Stage 3. Nonlinear modeling: We use the same inputs (lags) as the SARIMA model, obtained in Stage 2, for specifying the GSMN model described in (4). All the parameters of the hybrid model (1) are optimized simultaneously (including the parameters of the SARIMA model) by minimizing the conditional sum of the squared residuals (SSE) calculated as:

$$SSE = \sum e_t^2, \quad \text{with } e_t = y_t - L_t - N_t \quad (6)$$

using a gradient-based optimization technique.

Due to the presence of local optimum points, it is necessary to realize several runs of the optimization algorithm with different initial values for the parameters of the model. For each run, initial values for the hybrid model are specified as follows:

- For the linear model (SARIMA), we use the optimal parameter values calculated in Stage 2.
- For the GSMN model, the initial values are random following a uniform probability distribution with $w_i, u_j \in [-\delta, \delta]$ and $b_i, c_j \in [1 - \delta, 1 + \delta]$; we found that for $\delta = 0.1$, the optimization algorithm works fine.

In our case, we prefer the Broyden-Fletcher-Goldfarb-Shanno (BFGS) optimization algorithm.

3. ELECTRICITY DEMAND FORECAST

The proposed hybrid method is applied to forecast the monthly electricity demand (in GWh) in the Colombian Energy Market for the period from August 1995 (1995:8) to April 2010 (2010:4). All the models are estimated for the natural logarithm of the time series, but the measured forecasting errors are expressed in

terms of the original data. The first 155 observations were used for fitting the models and the last 24 observations for evaluating their forecasting ability; we use two forecast horizons: from 2008:5 to 2009:4 (12 months) and from 2008:5 to 2010:4 (24 months). For both horizons, we calculate one month ahead of forecasts. For each model fitted, we compute the mean absolute deviation (MAD) and the root of the mean squared error (RMSE).

In [10], the Box-Jenkins methodology [2] is applied to obtain a SARIMA model for this time series using the same fitting and forecasts periods. A SARIMA $(0,1,3) \times (1,1,2)_{12}$ is the preferred model when the `auto.arima()` function in the “forecast” package of Hyndman and Khandakar [11] is used for the automatic selection of the best configuration. The `auto.arima()` function implements a heuristic step-wise procedure for searching the configuration of a SARIMA model that minimizes the Akaike information criterion. In Table 1, we reproduce the error measures reported in [10] for the fitting and forecast periods.

The proposed specification methodology is applied as follows:

Stage 1. The transformed time series (using the natural logarithm function) is scaled to the interval $[-0.93, 0.93]$.

Stage 2. The Box-Jenkins methodology is applied to obtain a SARIMA model. In our case, it is the SARIMA $(0,1,3) \times (1,1,2)_{12}$ model reported in [10].

Stage 3. The SARIMA $(0,1,3) \times (1,1,2)_{12}$ model can be written as:

$$\begin{aligned} (1 - B)(1 - B^{12})(1 - \phi_{12}B^{12})y_t \\ = \mu \\ + (1 + \theta_1B + \theta_2B^2 + \theta_3B^3) \\ + \pi_1B^{12} + \pi_2B^{24})e_t \end{aligned} \quad (7)$$

By expanding both sides of the previous equation, we found that the lags for the autoregressive and moving average components are $\Phi = \{1, 12, 13, 24, 25\}$ and $\Theta = \{1, 2, 3, 12, 13, 14, 15, 24, 25, 26, 27\}$; see equation (4).

Table 1. Calculated errors

Model	Lags	Fitting	Forecasting	Forecasting
		MAD (RMSE)	MAD (RMSE) 12 months ahead	MAD (RMSE) 24 months ahead
SARIMA		36.11 (52.30)	51.88 (60.20)	58.82 (76.30)
Proposed model		* 35.93 (50.89)	* 47.68 (60.06)	* 52.87 (74.42)
GSMN-1	1-27	63.15 (82.00)	81.14 (105.59)	76.10 (99.42)
GSMN-2	1-21	63.71 (81.83)	81.00 (106.62)	76.23 (100.31)
GSMN-3	1-15	65.42 (84.45)	75.12 (103.82)	76.19 (101.71)
GSMN-4	1-14	68.33 (87.53)	81.98 (104.53)	78.16 (100.60)
GSMN-5	1-7, 12-16, 19-21	64.01 (82.58)	83.22 (114.36)	78.56 (107.33)
GSMN-6	1-3, 6, 12-15	65.34 (86.50)	80.14 (112.04)	77.91 (108.29)
GSMN-7	1-4, 6, 12-14	64.70 (85.30)	89.29 (115.80)	79.94 (108.06)

* Minimum values




Figure 1. Real values and forecasts obtained using the proposed model.

The final values of the parameters for the hybrid model are calculated by simultaneously optimizing the parameters of the SARIMA and GSMN components. The parameters are estimated by minimizing the conditional sum of squares of fitted residuals for $t = 28, \dots, 155$ and $e_1 = e_2 = \dots = e_{27} = 0$.

Also, we fit several GSMN models, as defined in (3), to the transformed and scaled time series. The parameters are estimated by minimizing the conditional sum of squares of fitted residuals for $t = k + 1, \dots, 155$ and $e_1 = \dots = e_k = 0$, where k is the maximum lag considered in the inputs of each model. The MAD and RMSE values for all models are summarized in Table 1.

By analyzing the statistics reported in Table 1, we conclude that the proposed hybrid model is able to forecast the values of the studied time series with better accuracy. In Figure 1, we plot the real values of the time series and the forecasted values calculated using the proposed model.

4. CONCLUSIONS

In this paper, we discuss a new hybrid model obtained by fusing a SARIMA model and a generalized single neuron model. The proposed model has several advantages: first, it is able to capture nonlinear behavior in the data; second, the SARIMA approach provides the modeler with a well-known and accepted methodology for model specification; and third, it is not necessary to use heuristics and expert knowledge for selecting the configuration of the artificial neural network because the GSMN model uses the same inputs as the SARIMA model and it is not necessary to specify processing layers as in other neural network architectures. To assess the effectiveness of our model, we forecast the monthly demand of electricity in the Colombian energy market using several competitive models and we compare the accuracy of forecasts. The results obtained show that our approach performs better than the SARIMA and GSMN models in isolation. However, further research is needed to gain more confidence and to better understand the proposed model.

REFERENCES

- [1] Zhang, G., Patuwo, E.B. and Hu, M.Y., Forecasting with Artificial Neural Networks: the State of the Art. *International Journal of Forecasting*: 14 (1), pp. 35-62, 1998.
- [2] Box, G.E.P. and Jenkins, G., *Time Series Analysis, Forecasting and Control*. Holden-Day, San Francisco, CA, 1970.
- [3] Zhang, G.P., Time Series Forecasting using a Hybrid ARIMA and Neural Network Model. *Neurocomputing*: 50, pp. 159 – 175, 2003.
- [4] Yadav, R.N., Kalra, P.K. and Jhon. J., Time Series Prediction with Single Multiplicative Neuron Model. *Applied Soft Computing*: 7(4), pp. 1157-1163, 2007.
- [5] Tseng, F.-M., Yu, H.-C. and Tzeng, G.-H., “Combining Neural Network Model with Seasonal Time Series ARIMA Model”. *Technological Forecasting & Social Change*: 69 (1), pp. 71-87, 2002.
- [6] Khashei, M. and Bijari, M., An Artificial Neural Network (p, d, q) Model for Time Series Forecasting. *Expert Systems with Applications*: 37 (1), pp. 479-489, 2010.
- [7] Aladag, C.H., Egrioglu, E. and Kadilar, C., Forecasting Nonlinear Time Series with a Hybrid Methodology. *Applied Mathematics Letters*: 22 (9), pp. 1467-1470, 2009.
- [8] Kaastra, I. and Boyd, M.m., Designing a Neural Network for Forecasting Financial and Economic Time Series. *Neurocomputing*: 10 (3), pp. 215-236, 1996.
- [9] Masters, T., *Practical Neural Network Recipes in C ++*. Academic Press, New York, 1993.
- [10] Vega, W., Velásquez, J.D. and Franco, C.J., Forecasting the Monthly Electricity Demand in the Colombian Energy Market using an SARIMA Model. Technical Report, Escuela de Sistemas, Universidad Nacional de Colombia, 2010.
- [11] Hyndman, R.J., and Khandakar, Y., Automatic Time Series Forecasting: The Forecast Package for R. *Journal of Statistical Software* (2008) 27 (3), 2008.